



# **A Preliminary Design Process for Airspace Systems**

**Initial Assessment - Chicago Case Study  
(VNTSC-DTS20-PDP-001)**

**NEXTOR**

**November 14, 2000**


**Bob Schwab, Technical Fellow**

**Boeing Air Traffic Management Services**



# NAS Architecture Evolution

Strategic Goals



**Options for the NAS**

- ¥ NAS Growth & Constraints
- ¥ Emerging Technologies
- ¥ Alternative Futures
- ¥ Globalization

**Phase 3**

- ¥ Far Term (2008-2020)
- ¥ Concept Architecture
- ¥ Technology Exploration

**Modernizing the NAS**

- ¥ NAS Performance
- ¥ NAS Safety Enhancement
- ¥ NAS Affordability

**Phase 2**

- ¥ Mid Term (2003-2007)
- ¥ Modernization Architecture
- ¥ New Functionality

**Sustaining the NAS**


- ¥ NAS Sustaining
- ¥ Funding Profiles
- ¥ Limited User Benefits
- ¥ Risk Management

**Phase 1**

- ¥ Near Term (2000-2002)
- ¥ Sustaining Architecture
- ¥ Committed Deployment




Today's Installed Base






# System Methods and Analysis Tools are Required





# An Architecture is Required for an Integrated Modeling, Simulation and Analysis Capability





# Case Study Approach

---

- ¥ **A Preliminary Design Process has been drafted**
  - **process needs to be validated**
  - **baselining and solution development must be grounded in real NAS performance needs**
  - **Case Study approach using several NAS operating regions to provide operational insight and real-world validation data**
- ¥ **Chicago is the initial Case Study airport/airspace region**
  - **some operational issues are specific, others are common to high-density complex terminal areas**
- ¥ **Additional Case Study regions to address overall NAS performance**
  - **comprehensive concept and technology exploration**
  - **sufficient scope to develop toolset requirements for NAS-wide trades**



# Preliminary Design Process, Phase 1

---

**Project sponsored by the NASA AATT program, Shahab Hasan**

**Project team:**

- Boeing Commercial Airplane Group (Aslaug Haraldsdottir, Bob Schwab)**
- Volpe Transportation Center (Dick Wright, Suzanne Chen, Bob Wisemann)**
- Logistics Management Institute (Pete Kostiuk)**
- Flight Transportation Associates (Bob Simpson)**
- NEXTOR (John Hansman)**
- FAA Coordinator Air Traffic Airspace Management (Bruce Ware)**



# Airline Schedule Models under Capacity Constraints

---

- ∞ **Accommodate growth by increasing fares and rationing demand in the face of scarce capacity**
- ∞ **Establish new hub airports to mitigate congestion at existing hubs**
- ∞ **Increase direct service to avoid congested hubs and gateways**
- ∞ **Move flights to off-peak times**
- ∞ **Increase nighttime operations**
- ∞ **Employ larger aircraft equipment, as opposed to growth in frequency**
- ∞ **Combination of five active strategies**



# Primary Operational Issues Identified

---

- 1. Slot control and insufficient gate capacity**
  - when slot control is lifted, gates will immediately limit growth
- 2. O Hare airfield complexity and configuration management**
  - wind changes
  - traffic demand
  - runway condition and intersecting runways
  - noise mitigation
- 3. Land And Hold Short Operations (LAHSO)**
  - maximum throughput is reduced 10% by new rules
  - further impact of turbojet growth





## Primary Operational Issues, continued

---

4. **Regional flow management**
  - Historically Validated Restrictions (miles-in-trail)
  - Swap Routes
  - Ground Stops, by phone TMU to TMU
  - coordination with Central Flow
5. **En route capacity**
  - growth in turbojets
  - National Routes Program
  - MIT restrictions in overhead streams to East coast
6. **Congestion at arrival fixes**
  - unbalanced arrival demand, runway utilization issue
  - high-altitude tailwinds, MIT up to 12 nm



## **Primary Operational Issues, continued**

---

### **7. Sever weather impact**

- weather forecasting accuracy**
- pilot/airline unpredictable reluctance to fly through storm cells**

### **8. Growth at nearby airports**


- Midway, airport construction, rapid growth**
- cargo operations during night**

### **9. Final approach spacing**

- VFR, runway occupancy**
- IFR, wake vortex rules**

### **10. Capacity of surrounding facilities**


- Cleveland Center, complexity and controller workload**
- MIT restrictions daily to East coast cities**



**Complex, Inter-Acting Constraints Dynamically Change Airport and Airspace Capacities**  
 Source: NASA Sponsored Airspace Preliminary Design Case Study




## Runway Capacity Coverage Curve - Chicago O'Hare (based on LMI Report - NASA CR-19928-207)





# Sample Statistical Analysis

Total Delay Time as Function of Weather and Volume



Source: Volpe Transportation Research Center



# Initial ETMS Capacity Data Characterizations


---

- < Cloud ceiling is a more important factor for arrival delay than for departure delay.
- < The above set of six independent factors can explain approximately one third of the variations in **total** delay time per flight. These selected set of weather and volume related factors could only explain approximately 17% of **gate** delay and 22% of **arrival** delay.
- < The stepwise regression model technique, when informed by a well-considered hypothesis, is an efficient way to understand the sensitivity of delay to other factors such as equipment outage, runway usage, and airspace congestion. Further analysis could be carried out.

Source: Volpe Transportation Research Center



# Operational Baseline Development Approach





# Case Study Conclusions

---

- ¥ **A Preliminary Design Process has been drafted**
  - **process needs to be validated**
  - **baselining and solution development must be grounded in real NAS performance needs**
  - **Case Study approach using several NAS operating regions to provide operational insight and real-world validation data**
- ¥ **Chicago is the initial Case Study airport/airspace region**
  - **some operational issues are specific, others are common to high-density complex terminal areas**
- ¥ **Additional Case Study regions to address overall NAS performance**
  - **comprehensive concept and technology exploration**
  - **sufficient scope to develop toolset requirements for NAS-wide trades**